

Building Solutions

**Ceramic tile adhesives
and grouts, waterproofing
and repair products**

info@constructionchemicals.com.au
www.constructionchemicals.com.au

Adelaide
49-57 Davis St
Wingfield SA 5013
Phone (08) 8243 7888
Fax (08) 8243 7800

Brisbane
45 Coulson St
Wacol QLD 4076
Phone (07) 3271 2944
Fax (07) 3271 3892

Darwin
4/4 Aristos Pl
(off Farrell Cres)
Winnellie NT 0820
Phone (08) 8947 1811
Fax (08) 8947 1819

Melbourne
11 Gabrielle Ct
Bayswater North VIC 3153
Phone (03) 9761 4711
Fax (03) 9761 4748

Perth
11 Collie St
Welshpool WA 6106
Phone (08) 9356 9999
Fax (08) 9356 9955

Sydney
31-33 Newton Rd
Wetherill Park NSW 2164
Phone (02) 9756 3533
Fax (02) 9756 3534

Auckland
16 Carpenter Rd
East Tamaki
Phone (09) 273 5444
Fax (09) 273 5442

Kuala Lumpur
Lot 2 Jalan Kecapi
33/2 Elite Industrial Estate
Off Jalan Bukit Kemuning
40000 Shah Alam
Phone (603) 5122 2522
Fax (603) 5122 2526

MATERIAL SAFETY DATA SHEET

Issued 01/07/2015
Colour Red

IDENTIFICATION

Product Name: **DRIVEWAY STAIN**
UN Number: 1866
Dangerous Goods Class: 3.2
Subsidiary Risk Class: Not Listed
Hazchem Code: 3(Y)
Packaging Group: III
Poisons Schedule: 8
Use: A clear or coloured stain for masonry surfaces.

Classified as hazardous according to criteria of Worksafe Australia.

Physical Description/Properties

Appearance: Colourless mobile liquid, strong odour
Boiling Point (°C) : Range 138 - 143
Vapour Pressure(kPa): 1.0 @ 20°C
Specific Gravity: 0.95 @ 15°C
Flash Point(°C): 24 ABEL
Flammability Limits: LEL: 1.0 UEL: 7.0
Solubility in Water: Below 0.1% mass

Ingredients	CAS No.	Proportion
Xylene	1330-20-7	70-80 %
Chlorinated Rubber		<20 %
Ingredients determined not hazardous		to 100 %

HEALTH HAZARD INFORMATION

Health Effects

Swallowed - May cause irritation to mouth, throat and digestive tract. Large dose may cause drowsiness and may lead to unconsciousness.

Eye - May be irritating to the eyes.

Skin - Irritant. Avoid prolonged or repeated contact as may cause dermatitis.

Inhaled - Vapour is irritant to mucous membranes and respiratory tract. vapour's can affect the central nervous system and result in headaches and dizziness. High concentrations of vapour, if exposure is prolonged, may cause unconsciousness. Aspiration of liquid into lungs can cause serious (even fatal) pneumonitis.

First Aid

Swallowed - If poisoning occurs, contact a doctor or Poisons information centre. If swallowed, do not induce vomiting. Give glass of water. If any suspicion of aspiration into lungs obtain medical advice immediately.

Eye - Irrigate with copious quantities of water. If soreness or redness persists, seek medical attention.

Skin - Wash off with soap and water. Remove contaminated clothing and laundry before re-use.

Inhalation - Move to fresh air, keep warm and at rest. Seek medical attention. Apply artificial respiration if not breathing.

Advice to Doctors

Because of risk of aspiration, gastric lavage should only be undertaken after endotracheal intubation.

PRECAUTIONS FOR USE

Exposure Limits - 100 ppm 8 hour time weighted average.

Ventilation - Avoid breathing vapour. Use in well ventilated area. Local exhaust ventilation usually required. Ensure ventilation is adequate to maintain air concentrations below exposure standards.

Personal Protection - Avoid eye and skin contact. Wear chemical goggles or face shield. Wear breathing apparatus in confined areas.

Flammability - Avoid heat and sources of ignition. Prevent build-up of flammable vapour's.

SAFE HANDLING INFORMATION

Storage and Transport - Avoid contact with strong oxidising agents. Store in cool well ventilated area away from heat and ignition sources. Containers should always be kept in storage properly labelled. Store only in original containers.

Spills and Disposal - Keep public away. Extinguish all ignition sources. For major spills, dam and recover. Prevent entry into drainage systems, rivers etc. Collect with absorbent material such as sand, earth or sawdust. Warn occupants downwind. Advise authorities. Ensure waste disposal conforms with local waste disposal regulations. After recovery and evaporation remaining soil may be disposed of to approved landfill, or if approved, allowed to degrade insitu.

Fire/Explosion Hazard - Flammable liquid. Combustion products include oxides of carbon. Use foam, CO₂, dry powder fire extinguishers. Use water sprays to cool fire exposed surfaces and any adjacent storage vessels. Shut off source of product if it is safe to do so. Remove sources of re-ignition. Vapour/Air mixture may ignite explosively. Flashback along vapour trail may occur.

All information in this data sheet is as accurate and up-to-date as possible. Since Construction Chemicals cannot anticipate or control the conditions under which this information may be used, each user should review the information in the specific context of the intended application. Construction Chemicals will not be responsible for damages of any nature resulting from use of or reliance upon the information.